

# **Technical Data Sheet**

info.elastomers@versalis.eni.com

# **DUTRAL**®

**TER 4334** 

EP(D)M

Ethylene - Propylene - Diene Terpolymer

Dutral<sup>®</sup> TER 4334 is an Ethylene - Propylene - Diene polymer produced by suspension polymerisation using a Ziegler-Natta Catalyst at the Ferrara production facility in Italy.

A non-staining antioxidant is added during the production process.

Main Properties	Unit	Typical Value
Mooney Viscosity ML 1+4(125 °C)	MU	28
Volatiles content	% wt	0.5 max
Ash content	% wt	0.3 max
Propylene content	% wt	27 <sup>(1)</sup>
ENB content	% wt	4.7 (1)
Oil content	% wt	30

<sup>(1)</sup> Referred to polymer matrix

### **Key Features**

Dutral<sup>®</sup> elastomers are characterized by excellent resistance to ageing and weathering, good resistance to both high and low temperatures, low permanent set values, good resistance to a large number of chemicals.

Dutral® TER 4334 is a general purpose semicrystalline terpolymer of medium-high molecular weight and medium diene content, extended with 30% of paraffinic oil.

It is characterized by high loading capacity and good green strength.

 $\mathsf{Dutral}^{\otimes}$  TER 4334 based compounds exhibit excellent extrusion properties, good dimensional stability, low swelling values and high curing rate.

# **Main Applications**

Automotive, cables, mechanical goods, buildings, appliances.

### **Physical Form**

Bales wrapped with low melting point polyethylene film; typical bale weight: 25 kg.

# **Packaging**

Cardboard box of 750 kg containing 30 bales (1050 x 1250 x h1050 mm).

### **Storage Conditions**

Store in vented, dry area at temperatures between 20°C and 30°C; no direct sunlight.

Shelf life: 36 months.

Please consult the relevant safety data sheet for more detailed information.

The information and data presented herein are to the best of our knowledge true and accurate, but no warranty or guarantee, expressed or implied, is made nor liability accepted with respect to the use of such information and data.

® Registered Trademark apr-12