

# Tecnoflon® FOR 60K

## fluoroelastomer

TECNOFLON® FOR 60K is a medium-low viscosity cure incorporated fluoroelastomers copolymer. This grade is designed to improve bonding in any application requiring adhesion to metal. In shaft seals or valve stem seals production, Tecnoflon® FOR 60K greatly reduces the reject rate due to adhesion problems.

Some of the basic properties of Tecnoflon® FOR 60K are:

- Superior bonding to metal
- Very good scorch safety
- Superior mold flow
- Lack of mold fouling

- Excellent hot tear resistance
- Excellent mold release

Tecnoflon® FOR 60K can be used for injection, compression, and transfer moulding of gaskets and seals. The product can be mixed using typical fluoroelastomers compounding ingredients and mixing can be accomplished with two-roll mills or internal mixers.

The material can be extruded into hoses or profiles and can be calendered to make sheet stocks or belting. Finished goods can be produced by a variety of rubber processing methods.

### General

Material Status	• Commercial: Active		
Availability	• Europe	• North America	
Features	• Bondability • Copolymer • Good Adhesion	• Good Mold Release • Good Tear Strength • High Flow	• Medium-low Viscosity
Uses	• Adhesives • Blending • Bonding	• Gaskets • Hose • Metal Bonding	• Profiles • Seals • Sheet
Appearance	• Off-White		
Forms	• Slab		
Processing Method	• Calendering • Compounding	• Compression Molding • Extrusion	• Injection Molding • Resin Transfer Molding

Physical	Typical Value	Unit	Test method
Mooney Viscosity <sup>1</sup> (ML 1+10, 121°C)	30	MU	No Standard
Fluorine Content <sup>1</sup>	66	%	No Standard

# Tecnoflon® FOR 60K

fluoroelastomer

---

## Notes

Typical properties: these are not to be construed as specifications.

<sup>1</sup> Raw polymer

---

**[www.solvay.com](http://www.solvay.com)**

**[SpecialtyPolymers.EMEA@solvay.com](mailto:SpecialtyPolymers.EMEA@solvay.com)** | Europe, Middle East and Africa

**[SpecialtyPolymers.Americas@solvay.com](mailto:SpecialtyPolymers.Americas@solvay.com)** | Americas

**[SpecialtyPolymers.Asia@solvay.com](mailto:SpecialtyPolymers.Asia@solvay.com)** | Asia and Australia



Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products. Neither Solvay Specialty Polymers nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Solvay's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Solvay's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. All trademarks and registered trademarks are property of the companies that comprise the Solvay Group or their respective owners.

© 2013 Solvay Specialty Polymers. All rights reserved.